

CUTTING MACHINE

C22 singlephase



Dimensions	
Effective	71 x 40 x h. 69
On Pallet	110 x 70 x h. 80

Weight	
Effective	Kg. 125
On Pallet	Kg. 135

Oil	with viscosity = 220
	Kg. 1,5

Electric Motor	220 Volt
	2 HP / 1,5 KW


Strokes / Minute	125
------------------	-----

Cutting capability	R. = 65 Kg. / mm ²			R. = 80 Kg. / mm ²		
		1 Ø 20	2 Ø 14	3 Ø 10	1 Ø 18	2 Ø 12

As preparation of the machine for the transport, we set it on a pallet (standard measures), cover it with a stiff carton paper and with a cellophane coat, and then fix it with plastic band.

Standard Equipment

Two blades in hardened steel, already fit on the machine



C22 Cutting Machine – Light and Practical

For small requirements (cutting bars with max. Ø 20 mm) the C 22 Cutting machine is ideal - available in both single-phase and three-phase versions.

It provides all the compact features and reliability of OF.ME.R cutting machines, but is small and light and therefore easy to handle, thanks too to a special steering bar and two rear rubber wheels.

Takes up very little room (71 x 40 x h. 69 cm).

A must for any worksite!



dm DELAHENTY MACHINERY PTY. LTD.
Machine Tool Merchants

14 Parkhurst Drive Knoxfield Victoria Australia 3180
Tel: (03) 9800 1544 Fax: (03) 9800 1344
www.delahenty.com.au

OF.ME.R. S.R.L.
Via Emilio Brasca, 137
20056 Trezzo S/Adda (MI) - ITALY
Phone: +39.2.90.90.134
Fax: +39.2.90.96.13.78