

CUTTING MACHINE

C36 "Euro" threephase



Dimensions	
Effective	100 x 70 x h. 84
On Pallet	110 x 70 x h. 95

Weight	
Effective	Kg. 375
On Pallet	Kg. 385

Oil	with viscosity = 220
	Kg. 2,5

Electric Motor	380 Volt
	4 HP / 3 KW

Strokes / Minute	65
------------------	----

Cutting capability	R. = 65 Kg. / mm ²			R. = 80 Kg. / mm ²		
		1 Ø 30	2 Ø 20	3 Ø 16	1 Ø 26	2 Ø 18

As preparation of the machine for the transport, we set it on a pallet (standard measures), cover it with a stiff carton paper and with a cellophane coat, and then fix it with plastic band.

Standard Equipment	Optionals	
<p>Blades Two blades in hardened steel already fit on the machine</p>	<p>Lubricating Pump Special manual pump with flow adjuster, for constant and easy lubrication of all the parts liable to seizure. It is easy to use. Simply press the batching cylinder control knob once a day, in case of daily use, and regulate the cutting machine.</p>	<p>Movable Pedal An additional accessory for the "Euro" cutting machine is a mechanical moving pedal unit for remote control. Thanks to this unit, once the machine has been placed on a supporting surface, the operator can maintain a correct posture during work.</p>



dm DELAHENTY MACHINERY PTY. LTD.
Machine Tool Merchants

14 Parkhurst Drive Knoxfield Victoria Australia 3180
Tel: (03) 9800 1544 Fax: (03) 9800 1344
www.delahenty.com.au

OF.ME.R. S.R.L.
Via Emilio Brasca, 137
20056 Trezzo S/Adda (MI) - ITALY
Phone: +39.2.90.90.134
Fax: +39.2.90.96.13.78