

COMBINED MACHINE

TP24/28 singlephase "Inverter"



Dimensions	
Effective	82 x 105 x h. 85
On Pallet	80 x 105 x h. 100

Weight	
Effective	Kg. 390
On Pallet	Kg. 400

Oil	with viscosity = 220
	Kg. 5

Electric Motor	220 Volt
	3 HP / 2,2 KW


Turns / Minute	10
----------------	----

Cutting / Bending capability	R. = 65 Kg. / mm ²			R. = 85 Kg. / mm ²		
		1 Ø 22/26	2 Ø 16/18	3 Ø 12/14	1 Ø 20/24	2 Ø 14/16

As preparation of the machine for the transport, we set it on a pallet (standard measures), cover it with a stiff carton paper and with a cellophane coat, and then fix it with plastic band.

Standard Equipment

- 1 hardened square pin;
- 1 hardened stirrup bending pin;
- 3 hardened bush holding pins;
- 1 checking block;
- 1 pedal for remote control;
- 1 bush Ø 50; 1 bush Ø 60;
- 1 bush Ø 70; 1 bush Ø 80;
- Two blades in hardened steel.



Optionals



Stirrup linear measurer

Device for measuring the length of the bars - can be fitted to both side of the machine.
For impeccable precision!



Stirrup bending tool

Can be used from both sides of the machine.
When suitably fitted with the pins and bushes provided, up to three bars can be bent at the same time at max. 180 .
A big saving of time and effort!



dm DELAHENTY MACHINERY PTY. LTD.
Machine Tool Merchants

14 Parkhurst Drive Knoxfield Victoria Australia 3180
Tel: (03) 9800 1544 Fax: (03) 9800 1344
www.delahenty.com.au

OF.ME.R. S.R.L.
Via Emilio Brasca, 137
20056 Trezzo S/Adda (MI) - ITALY
Phone: +39.2.90.90.134
Fax: +39.2.90.96.13.78