

COMBINED MACHINE TP38/45 threephase




Dimensions	
Effective	104 x 122 x h. 89
On Pallet	105 x 120 x h. 105
Weight	
Effective	Kg. 800
On Pallet	Kg. 810
Oil	with viscosity = 220
	Kg. 13
Self-Breaking Electric Motor	380 Volt
	5,5 HP / 4 KW
Turns / Minute	9

Cutting / Bending capability	R. = 65 Kg. / mm ²			R. = 85 Kg. / mm ²		
		1 Ø 30/40	2 Ø 22/28	3 Ø 20/24	1 Ø 28/36	2 Ø 26/26

As preparation of the machine for the transport, we set it on a pallet (standard measures), cover it with a stiff carton paper and with a cellophane coat, and then fix it with plastic band.

Standard Equipment

- 1 hardened square pin;
- 1 hardened stirrup bending pin;
- 3 hardened bush holding pins;
- 1 checking block; 1 pedal for remote control;
- 1 bush Ø 50; 1 bush Ø 60;
- 1 bush Ø 70; 1 bush Ø 80;
- 1 bush Ø 95; 1 bush Ø 120;
- Two blades in hardened steel.



Long saddles are indispensable for double bending.

Long Saddles

Optionals



Stirrup linear measurer

Device for measuring the length of the bars - can be fitted to both side of the machine. For impeccable precision!



Stirrup bending tool

Can be used from both sides of the machine. When suitably fitted with the pins and bushes provided, up to three bars can be bent at the same time at max. 180°. A big saving of time and effort!



ANGLE CONTROL

The special Computer Angle Control can be fitted on all threephase Bending and Combined Machines. Operation of the machines featuring Angle Control can be automatic or manual. Computerised pre-selection offers up to 10 bending programs, with different angles and directions of rotation.



dm DELAHENTY MACHINERY PTY. LTD.
Machine Tool Merchants

14 Parkhurst Drive Knoxfield Victoria Australia 3180
Tel: (03) 9800 1544 Fax: (03) 9800 1344
www.delahenty.com.au

OF.ME.R. S.R.L.
Via Emilio Brasca, 137
20056 Trezzo S/Adda (MI) - ITALY
Phone: +39.2.90.90.134
Fax: +39.2.90.96.13.78