

STIRRUP BENDER

ST16 "Rapida" threephase



Dimensions	
Effective	80 x 70 x h. 96
On Pallet	110 x 70 x h. 60

Weight	
Effective	Kg. 155
On Pallet	Kg. 160

Oil	with viscosity = 220
	Kg. 2

Electric Motor	380 Volt
	2 HP / 1,5 KW

Turns / Minute	21
----------------	----

Number of rods which may be bent simultaneously	N.	1	2	3	4	7	10
		Ø	16	12	10	8	6

As preparation of the machine for the transport, we set it on a pallet (standard measures), cover it with a stiff carton paper and with a cellophane coat, and then fix it with plastic band.

Standard Equipment



- 1 square pin;
- 1 stirrup bending pin;
- 1 stirrup bending pin Ø16;
- 3 bush holding pins;
- 1 checking block; 1 pedal;
- 1 bush Ø 50; 1 bush Ø 60.



Stirrup linear measurer

Device for measuring the length of the bars. For impeccable precision!

Optionals



Stirrup bending tool

When suitably fitted with the pins and bushes provided, up to three bars can be bent at the same time at max. 180°. A big saving of time and effort!



Electric panel and tool-holding box



dm DELAHENTY MACHINERY PTY. LTD.
Machine Tool Merchants

14 Parkhurst Drive Knoxfield Victoria Australia 3180
Tel: (03) 9800 1544 Fax: (03) 9800 1344
www.delahenty.com.au

OF.ME.R. S.R.L.
Via Emilio Brasca, 137
20056 Trezzo S/Adda (MI) - ITALY
Phone: +39.2.90.90.134
Fax: +39.2.90.96.13.78