



5 | BASIC 270/60



□ 0°	250	200	270x200	3~	1 0 2	1.5/1.3	38/76	mm. 270	H 27	252	B 800		
▤ 45°	180	170	200x80						s 0.9		L 1700		
▥ 60°	110	100	90x150						L 3090		H 2050	h 935	

dm DELAHENTY MACHINERY PTY. LTD.
Machine Tool Merchants

14 Parkhurst Drive Knoxfield Victoria Australia 3180
Tel: (03) 9800 1544 Fax: (03) 9800 1344
www.delahenty.com.au



- Manual bandsaw, mitre cutting from 0° to 60° left
- Vice with quick motion and clamping, jaws height 140 mm
- Easy stops at 0°, 45° and 60° left; graduated plate to identify different angles
- Adjustment of the blade tension from the front side of the sawframe, checked by an end-stroke
- Blade tension 1500 kg/cm², blade guides with hard metal pads
- Steel sawframe with tubular section, pulleys with 320mm diameter
- Start-button inside the handle
- Removable coolant tank and electro-pump; bi-metal blade
- Floor stand with room in the back
- Tools and user's book
- In compliance with CEE Safety and Electro-magnetic Compatibility Norms (EMC)
- Electrics according to the Norms EN60204-1, EN55011, EN50082-2
- **CARTON BOX PACKING INCLUDED**