



	CSAV		CS60V		PRESTAZIONI MASSIME CON RULLI STANDARD MAX. PERFORMANCES WITH STANDARD ROLLS HOECHSTE LEISTUNGEN MIT NORMAL WALZEN CAPACITES MAX. AVEC GALETS STANDARD CAPACIDADES MAX. CON RODILLOS STANDARD
	50x10	∅ 700	60x12	∅ 800	
	60x20	∅ 600	100x20	∅ 1000	
	30	∅ 1200	35	∅ 800	
	50	∅ 1000	60	∅ 700	
	50	∅ 1000	60	∅ 900	
	50	∅ 800	60	∅ 900	

	45	∅ 1000	50	∅ 700
	30	∅ 800	40	∅ 800
	1" 1/2	∅ 800	2"	∅ 1000
	60 x 2	∅ 1000	70 x 2	∅ 1500
	60 x 30	∅ 800	80 x 45	∅ 750
	60 x 30	∅ 800	80 x 45	∅ 850
	50 x 25	∅ 2000	60 x 30	∅ 2500
	50	∅ 2000	60	∅ 3500
	50 x 25	∅ 1200	80 x 30	∅ 5000
	60 x 30	∅ 2000	100 x 40	∅ 6000
	60 x 25	∅ 800	80 x 40	∅ 1000

PRESTAZIONI MASSIME CON RULLI SPECIALI
 MAX. PERFORMANCES WITH SPECIAL ROLLS
 HOECHSTE LEISTUNGEN MIT SONDERWALZEN
 CAPACITES MAX. AVEC GALETS SPECIAUX
 CAPACIDADES MAX. CON RODILLOS ESPECIALES

	CSAV CSAV H	CS60V CS60V H
<ul style="list-style-type: none"> ∅ alberi ∅ shafts ∅ Achsen ∅ axes ∅ ejes 	40 mm.	50 mm.
<ul style="list-style-type: none"> ∅ rullo superiore ∅ upper roll ∅ Achsen ∅ galet supérieur ∅ rodillo superior 	135 mm.	165 mm.
n. giri/min. rulli N. R.P.M. rolls U/Min. walzen Tours/mn. galets giros ejes/pm.	12	12
Motore Motor Motor Moteur Motor	2,2 kW	3 kW
Centralina H H gearbox H - aggregat Centrale H Centralita H	1,1 kW	1,5 kW
Cilindro H Cylinder H H Zylinder CYLINDRE H Cilindro H	7 t.	10 t.
Peso Weight Gewicht Poids Peso	Kg. 300 / 375	Kg. 400 / 475
Ingombri Dimensions Aussenmasse Encombrements Dimensiones	1140 / 700 h. 1400	1450 / 700 h. 1440

